



For iOS Lightning devices, USB Type-C devices and Computers

Dual-head Lavalier Microphone
with **headphone monitoring**
and **input level control**

LavMicro+DC2M



- ① Dual-head Lavalier Microphone
- ② Input Level Control Wheel
- ③ 3.5mm Headphone Output
- ④ Lightning Connector
- ⑤ USB Type-C Connector
- ⑥ USB Type-A Connector

Features

- Omnidirectional condenser dual-head lavalier microphone
- Three detachable output cables for iOS Lightning connector devices, USB Type-C connector devices (including PC with Type-C connector) and computers
- 3.5mm headphone monitor jack
- Input level control wheel
- Compact and lightweight

Specifications

Audio Output Jack	USB Type-C connector
Sensitivity	-42+/-3dB (0dB=1V/Pa, at 1KHz)
Polar Pattern	Omnidirectional
Signal to Noise Ratio	58 dB S:(f=1KHz, S.P.L=1Pa) N:(A-Weighted curve)
Frequency Response	40Hz-20kHz
Gain	0-30 dB
Sampling Frequency	44.1 kHz / 48 kHz / 96kHz
Bitrate	16Bit / 24Bit
Power Requirement	Supplied by iOS Device, Android Device or Computer
Output Cables	USB Type-C to Lightning USB Type-C to USB Type-C USB Type-C to USB Type-A
Weight	70g (2.5 oz)
Cable Length	1.7m (5.7ft)